

DATA SPHERE

Data at your command.



RatPac's Data Sphere is today's answer to data distribution in the professional entertainment industry. Meets all ETL/CSA standards.



DATA SPHERE

SWITCH: 16 PORT 1 GIGABIT UNMANAGED ETHERNET SWITCH WITH ACTIVITY LIGHTS
8 PORTS ON FACE AND 2 PORTS ON BACK

WIRELESS DATA

2 UNIVERSES CRMX TIMO 2. TRANSMIT OR RECEIVE. EXTERNAL NON REMOVABLE 3.4 dbi ANTENNA'S

INTERNAL RECHARGEABLE BATTERY ALLOWS CONFIGURATION WITHOUT POWER
BUILT-IN BATTERY ALLOWS FOR 45 MINUTES OF SET UP TIME. RECHARGES WITH AC INPUT
DESIGNED AND ASSEMBLED IN CALIFORNIA
HINGED FOR EASY SERVICE.

RUGGED CONSTRUCTION

FEATURES

8 UNIVERSE DMX NODE, WITH 8 INDIVIDUALLY CONFIGURABLE XLR OUTPUT PORTS WITH SEPARATE UNIVERSES AND CAPABILITY.
CUSTOMIZABLE UNIVERSE AND INDICATION
COLOR IDENTIFICATION

COPY FUNCTION

COPY OVER THE DMX UNIVERSE AND ASSOCIATED COLOR FROM ONE XLR PORT

OPTOSPLITTER:

2 OPTICALLY ISOLATED 4 PORT DMX SPLITTERS. DMX UNIVERSE FOR BOTH ARE DETERMINED BY THE NODE PORT (A OR E) CONNECTED TO THE OPTOSPLITTER

RIGGING

SEVERAL RIGGING POINTS ARE PROVIDED, 3/8"-16 AND 1/4"-20 THREADED FEMALE INSERTS
RACK MOUNTABLE: HARDWARE IS INCLUDED

GUI

LARGE/BRIGHT DISPLAY FOR EASY USE
INTERFACE FUNCTIONS:
SET DMX PROTOCOLS: ArtNet, sACN, UNICAST, MULTICAST.
DIRECT DMX INPUT FOR WIRELESS DMX.
CONFIGURE NETWORK PROTOCOLS.
SUBNET MASK, DEVICE IP
EASILY ACCESSED FROM ANY BROWSER

DIM FUNCTION

4 BRIGHTNESS LEVELS FOR LED INDICATOR LIGHTS SELECTABLE W/BUTTON PRESS
QUIET OPERATION FOR USE ON SET. LOW RPM FANS THERMOSTATICALLY CONTROLLED RUN ONLY WHEN NEEDED

DIMENSIONS

17.05"X9.27"X8.24" WEIGHT: 13.5 LBS

POWER IN

20 AMP POWERCONN 20A BREAKER PROTECTION
POWERCONN/EDISON ADAPTER PROVIDED.
1 PORT POE 30 WATTS DC INPUT FOR EXTENDED USE W/EXTERNAL BATTERY
12V-14V DC

MODEL

531.0241.001.0A



CLICK FOR VIDEO INSTRUCTION

TECH SUPPORT



"QUIET ON SET."