



RATPAC 24 CHANNEL DUO 24x1.2 kW/12x2.4 kW 20 INCH DIMMER

Large-format dimming with more flexibility.



We've combined everything great about the V3 12x2.4 and the V3 24x1.2 units and rolled them into one whisper quiet dimmer. We call it the 24 Channel Duo. Taking what we learned with developing the Unity's configurable, dimmable, 2.4kW or 1.2kW duplex power outputs, we've made a more versatile twenty-inch dimmer. A built-in wireless CRMX transmitter/receiver enables all channels to be controlled with or without a DMX cable.

RATPAC 24 CHANNEL DUO 20 INCH DIMMER

INPUT: 120/208 VAC 3 PHASE E1016 CAMLOK
OUTPUT: 2 SOCAPEX, 12 CHANNELS AT 2.4kW PER CHANNEL OR 4 SOCAPEX, 24 CHANNELS AT 1.2kW PER CHANNEL. ONE 5V USB-A COURTESY CHARGE PORT FOR MOBILE DEVICES.

CONTROL

SELF-TERMINATING DMX 5-PIN XLR I/O
PASS-THRU
WIRELESS ADDRESSABLE CRMX RECEIVER OR TRANSMITTER
MANUAL BUMP BUTTON, BI-COLOR INDICATED
DIM/NON-DIM DIP SWITCHES

FEATURES

WHISPER QUIET TECHNOLOGY
RUGGED ANCHOR POINTS FOR RIGGING

FEATURES

MULTI-CHANNEL ELECTRONIC GHOST LOAD
IMPROVES DIMMING STABILITY FOR LOW WATTAGE INCANDESCENT BULBS & DIMMABLE LED FIXTURES
NEW INDUCTORS INCREASE DIMMING RELIABILITY WHILE REDUCING NOISE
ISOLATED SWITCHING HELPS ELIMINATE LAMP FLICKER
ETL AND CSA LISTED

DIMMING DEVICE

120 VAC 20A SOLID STATE RELAYS

OVERLOAD PROTECTION

20 A AND 10A RESETTABLE BREAKERS

DIMENSIONS

8"H x 20"W x 20"D

WEIGHT: 78 LBS

INCLUDED IN THE BOX

ONE 24 CHANNEL DUO DIMMER
ONE 5dB RPTNC ANTENNA

MODEL

531.0284.001.0A (US)
531.0285.001.0A (CDA)



TECH SUPPORT



"QUIET ON SET."