

LIMITLESS CONTROL ON THE FLY



SLINGSHOT 200

The Slingshot 200 is a compact single-channel dimmer that supports wireless DMX control and has a maximum load capacity of 200 watts. It's an ideal choice for on-set practical fixtures as it features passive cooling for very quiet operation. The incorporated TimoTwo chip enables CRMX in both RX or TX modes and CRMX2 to be used with other CRMX2-capable devices.

The Slingshot 200 has WiFi node/gateway capability using sACN or Art-Net from your control software. This feature is useful for receiving DMX control and sending out a CRMX2 wireless signal to other units on set. It also has the option to input or output via the hardline 5-pin DMX connector. Plus, it comes with two side-mounted Edison dimmer output connectors that make placement easy.

The Slingshot 200 has an internal battery that is useful for setup and programming. Dimming is achieved with a hardline AC Edison attached via the convenient flat swivel Edison connector to powerCON TRUE1 input. You can rig the Slingshot 200 using the two handy 1/4"-20 screw mounts on its body. The programming process is very fast using its built-in on-screen menu system with a selection wheel/push button or via the web GUI on its WiFi connection.

For on-set applications, the screen display provides a Fixture/Universe/Address label for easy identification. The Slingshot 200 offers adjustable dimmer curves for Incandescent/LED/Switchable/Hot Power for your control and practical needs.

RENT SLINGSHOT 200

FEATURES:

CUSTOM DESIGNED FOR 120V LED TUBES AND LOW-WATTAGE PRACTICALS
 RATED AT 200W, WITH OVER-CURRENT AND OVER-TEMPERATURE PROTECTION
 PROVIDES A SMOOTH DIM FROM 0-100% AND 100%-0%

BUILT-IN CRMX WIRELESS TRANSMITTER WITH 400 FEET RANGE
 COMPATIBLE WITH ALL WIRELESS RATPAC AND CRMX BASED PRODUCTS

TWO 2.4GHZ EMBEDDED ANTENNAS FOR CRMX AND WIFI
 STATUS QUO WITH TIMEOUT OPTIONS
 AUTO AND CONFIGURABLE TIME FOR SCREEN-OFF AND BUTTON LOCK
 STATUS AND CONTROLS THROUGH WEB GUI (WIFI)

MODE SELECT:

INCANDESCENT: SAME AS LUNCHBOX DIM CURVE

LED DIM: SAME AS LEGACY 12X200 DIM CURVE

SWITCHABLE: <50%: OFF, >50%: ON
 HOT POWER

INPUT:

POWERCON TRUE1 TOP, 120VAC 2A 200W
 CONVENIENT ROTATING AC PLUG TO TRUEONE PIGTAIL CABLE

MAX OUTPUT:

200W DIMMING CONTROLLED
 TWO BLACK EDISON OUTPUTS

DATA INPUT SOURCE:

5-PIN XLR INPUT FOR DMX512 (8-BIT OR 16-BIT RESOLUTION)
 WIRELESS CRMX RECEIVE
 WIFI (ARTNET AND SACN PROTOCOLS)
 MANUAL

DATA OUTPUT OPTIONS:

WIRELESS CRMX TRANSMIT
 XLR PORT

PRIMARY PROTECTION WITH FAULT INDICATOR:

FAST OVER CURRENT > 7A
 OVER TEMPERATURE

SECONDARY PROTECTION:

2A THERMAL CIRCUIT BREAKER, SLOW PROTECTION FOR < 7A
 SHORT CIRCUIT
 RESETTABLE

DIMENSIONS:

3.93" X 3.36" X 2.60"

WEIGHT:

.96 LBS

MODEL:

SLINGSHOT 200

ETL LISTED FOR US & CANADA

AVAILABLE IN KITS OF 2, 6, OR 12 WITH AC INPUT CABLES AND RIGGING ACCESSORIES



SLINGSHOT DATA ROUTING OPTIONS

IF INPUT IS...	IF INPUT IS VIA WIFI	IF INPUT IS VIA CRMX	IF INPUT IS VIA XLR	IF INPUT IS SET MANUALLY
THEN OUTPUT CAN BE VIA WIFI?	NO	NO	NO	NO

THEN OUTPUT CAN BE VIA CRMX?	YES	NO	YES	YES
THEN OUTPUT CAN BE VIA XLR?	YES	YES	YES (WITH ACCESSORY Y-CABLE)	YES

YOU MAY ALSO CONSIDER...

AKS +
 Imagine controlling lighting levels from your iPhone or tablet! Whether from your DIT tent, follow car, or right on set, the AKS Plus gives you full control. Small enough to fit in your hand, powerful enough to run your lights through a wireless transmitter and an Art-Net DMX node: An all in one unit powered by over 20 hours of...



[Back to Single Channel Dimming Control](#)

1:16

1:16

▶

⌂

+

Locations

- Los Angeles
- Headquarters
- Atlanta
- New York
- Vancouver
- Toronto

Community

- Tech Support
- Videos
- Team RatPac
- Careers
- Terms & Conditions
- Contact

Follow

